



TSi POWER (P) LTD,
 PLOT NO. 154-155, SIDDHI
 INDUSTRIAL INFRASTRUCTURE
 PARK, WAGHODIA, VADODARA-
 391760, GUJARAT, INDIA
 e-mail : info@tsipower.in
 Ph: +91 8000455999

Specifications sheet: Fast Correction PWM Automatic Voltage Regulator (AVR), $\pm 12\%$ series

CATEGORY	FEATURE	THREE PHASE MODEL (PANEL TYPE) VRp-200000-9339-120P
ELECTRICAL	Capacity in KVA (KW)	200 KVA
	Regulator engine	High frequency 20 Khz IGBT driven voltage regulation convertor
INPUT	*Nominal voltage	400 volts ac, three phase
	*Normal operating voltage (typical output regulation within +/- 1% of nominal)	352 - 448 volts ac for full regulation
	Relaxed operating voltage (relaxed output regulation within functional range of 200-250V P-N)	305 - 485 volts ac within maximum rated input current capacity
	Maximum rated input current	328 A
	Nominal frequency	47 - 63 Hz
	Input circuit breaker rating	400A X 3 phase MCCB
	Input wire size	BUS BAR
OUTPUT	Ac connection	L1in , L2in, L3in, neutral and ground bus bar provided
	*Nominal voltage	400 volts ac, three phase
	Power efficiency	typically over 97 % (with 20 - 100% load conditions)
	Voltage regulation (typical, excluding meter error)	+/- 3%
	Maximum rated output current	289 A
	System status indicator	Green LED (ON) indicates Normal (regulating mode) operation
	Ac connection	L1in , L2in, L3in, neutral and ground bus bar provided
PHYSICAL	Dimensions (IN MM) approx.	650 D x 1000 W x 2000 H
	Weight (approx.)	490 Kgs
	Display	Digital output voltage display thru selector switch
	Annunciation	LED display for Regulation mode, Bypass mode & Fault conditions
	Mounting	Pad Mounted
ENVIRONMENTAL	Ambient temperature	0 ^o to + 45 ^o centigrade (32 ^o to +113 ^o farhenite). 10 to 90% RH non-condensing
	Cooling method	Fan Cooled
PROTECTIVE FEATURES	Standards & Safety	Designed to meet UL 60950-1 standards. Protection class IP 20.
	Overload & Short Circuit Protection	Through suitably rated input circuit breaker
	Soft Switch-On	This feature ensure that output voltage is never higher than input voltage upon switch-on, before it commences full stabilization.
	Automatic bypass	Automatic bypass will be activated when there is a fault condition
	Surge Test Conditions	Per Class 2 Surge (combination wave) 1.2 X 50µs, 6kV, 8 X 20 µs, 3 kA waveform. L-N < 300V
NOTES	Surge let-through voltages	1.2 X 50µs, 6kV, 8 X 20 µs, 3 kA waveform. L-N < 300V
	<p>1. All * marked voltage regulation ranges are based on 400V nominal output voltage. They would proportionately change in case nominal output voltage is required to be preset at any other value between 380-415V.</p> <p>2. All models of VRp's are optionally available with 400 Volts to 200 Volts step down transformers in a separate cubical.</p> <p>3. Please ask if any non-standard range or customised feature is required.</p> <p>4. Since our designs are constantly evolving, the above specifications are liable to change without prior notice.</p>	