



TSI POWER (P) LTD,
 PLOT NO. 154-155, SIDDHI
 INDUSTRIAL INFRASTRUCTURE PARK,
 WAGHODIA, VADODARA-391760,
 GUJARAT, INDIA
 e-mail: info@tsipower.in
 Ph: +91 8000455999

Specifications sheet: VRP Precision PWM Line Conditioners for Machinery, $\pm 13\%$ series

CATEGORY	FEATURE	SINGLE PHASE MODEL
		VRP-8000-9230-130M
ELECTRICAL	Capacity in KVA (KW)	8 KVA
	Regulator engine	High frequency 20 Khz IGBT driven voltage regulation convertor
INPUT	Nominal voltage	240 volts ac, single phase
	*Normal operating voltage (typical output regulation within +/- 1% of nominal)	207 - 271 volts ac for full regulation
	Relaxed operating voltage (relaxed output regulation within functional range of 200-250V P-N)	173 - 283 volts ac within maximum rated input current capacity
	Maximum rated input current	39A
	Nominal frequency	47 - 63 Hz
	Input circuit breaker rating	40 A X 2 phase (ganged MCB)
	Input wire size	6 mm ² (AWG 10)
	Ac connection	Terminal block (L1in, neutral and ground wires) provided
OUTPUT	Nominal voltage	240 volts ac, single phase
	Power efficiency	typically over 97 % (with 20 - 100% load conditions)
	Voltage regulation (typical, excluding meter error)	+/- 1%
	Maximum rated output current	33A
	System status indicator	Green LED (ON) indicates Normal (regulating mode) operation
	Ac connection	Terminal block (L1op, neutral and ground wires) provided
PHYSICAL	Dimensions (IN MM)	435D x 300W x 175H
	Weight (approx.)	30 Kgs
	Annunciation	LED display for Regulation mode, Bypass mode & Fault conditions
	Mounting	Pad mounted
ENVIRONMENTAL	Ambient temperature	0 ^o to + 45 ^o centigrade (32 ^o to +113 ^o fahrenheit). 10 to 90% RH non-condensing
	Cooling method	Fan Cooled
PROTECTIVE FEATURES	Standards & Safety	Designed to meet UL 60950-1 standards. Protection class IP 20.
	OV/UV cut off with SPP	Automatic trip in event of High/Low/Missing Voltage
	Overload & Short Circuit Protection	Through suitably rated input circuit breaker
	Soft Switch-On	This feature ensure that output voltage is never higher than input voltage upon switch-on, before it commences full stabilization.
	Automatic bypass	Automatic bypass will be activated when there is a fault condition
	Surge Test Conditions	Per Class 2 Surge (combination wave)
	Surge let-through voltages	1.2 X 50 μ s, 6kV, 8 X 20 μ s, 3 kA waveform. L-N < 300V
WARRANTY	Warranty	Two year limited warranty, covering repair/replacement of defective parts
NOTE	The star (*) marked voltage regulation range is based on 240V nominal output voltage. This would proportionately change in case nominal output voltage is required to be preset at any other value between 215-240V.	